C8M 35' COACH

SIDE

RDE



BATTERY ELECTRIC • ZERO-EMISSIONS • SAFEST BATTERIES

0

C8M 35' COACH BUS 100% Battery Electric







SPECIFICATIONS

ZF front axle

315/80R22.5

BYD in-wheel drive axle

mechanical leveling valves

Front & rear disc-brakes, ABS

Air suspension with

DIMENSIONS

Length Width Height Wheelbase Curb Weight GVWR Seats Wheelchair Positions

PERFORMANCE

Top Speed Range¹ Turning Radius Approach Angle Departure Angle

35.2 ft. 102 in. 140 in. 240.2 in. 31,970 lbs. 41,888 lbs. Up to 41 + 1 2/0

65 mph

39 ft.

≥8.6°

≥8.6°

149 miles

POWERTRAIN

CHASSIS

Front Axle

Rear Axle

Brakes

Tires

Suspension

Motor Type Max Power Max Torque Battery Type Battery Capacity² Charging Time³ Charging Capacity⁴

Asynchronous Motor 3 Phase 180 kW×2 1500 N·m×2 BYD LFP Battery 313 kWh 2-2.5 h J1772 DC 150kW

Notes:

All information based on the latest data available at the time of printing. Final specs subject to change at production. 1. Variables affecting range include air

 Variables arrecting range include air temperature, weather, grade, speed, driver habits and use of air conditioning and heating.
Initial battery capacity shown. May decrease with time and use.
Battery age and outside ambient temperature

affect charging times. 4. AC, overhead and inductive charging options available.



Real Innovation Delivered with Excellence[™]