

G.





BATTERY ELECTRIC • ZERO EMISSIONS • SAFEST BATTERIES

# **K9MD 40' TRANSIT BUS** 100% Battery Electric







# SPECIFICATIONS

ZF front axle

305/70R22.5

RIDE in-wheel drive axle

mechanical leveling valves

Front & rear disc-brakes, ABS

Air suspension with

### DIMENSIONS

Length Width Height Wheelbase Curb Weight GVWR Seats Wheelchair Positions

### PERFORMANCE

Top Speed Range<sup>1</sup> Turning Radius Approach Angle Departure Angle

#### 40.9 ft. 102 in. 134 in. 284 in. 35,140 lbs. 44,754 lbs. Up to 42 + 1 2

65 mph

43.6 ft.

≥8.6°

≥8.6°

203 miles

CHASSIS

Front Axle

Rear Axle

Brakes

Tires

Suspension

POWERTRAIN Motor Type Max Power Max Torque Battery Type Battery Capacity<sup>2</sup> Charging Time<sup>3</sup> Charging Capacity<sup>4</sup>

Asynchronous Motor 3 Phase 180 kW×2 1500 N·m×2 RIDE LFP Battery 455 kWh 3-3.5h J1772 DC 150kW

#### Notes:

#### All information based on the latest data available at the time of printing. Final specs subject to change at production. 1. Variables affecting range include air

 Variables affecting range include air temperature, weather, grade, speed, driver habits and use of air conditioning and heating.
Initial battery capacity shown. May decrease with time and use.
Battery age and outside ambient temperature affect charging times.
A.C, overhead and inductive charging options

4. AC, overhead and inductive charging options available.



# **Real Innovation Delivered with Excellence**<sup>™</sup>